



## Series switch flush mount, BJ

Compatible with Busch-Jaeger switch ranges

EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588394988	0300/9498	130 g	70 g	7.00 x 7.00 x 4.50 cm	11.50 x 10.50 x 5.80 cm

### TOP FEATURES

Integration/control with TechniSat CONNECT

Device for flush mounting in standard device boxes

Compatible with Busch-Jaeger switch ranges

Measuring of energy consumption

Integrated scene control

Integrated Z-Wave™ repeater function

Electronic overload protection

### AMBIENT STORAGE CONDITIONS

Temperature: -20 ... 60 °C

Humidity: 5 ... 90 %

### AMBIENT OPERATING CONDITIONS

IP class: 20

Ambient temperature: 5 ... 35 °C

Humidity: 10 ... 75 %

### FUNK COMMUNICATION

Telecommunication: Z-Wave Plus

funk\_security\_s2: Yes

funk\_smartstart: Yes

Range inside: max. 40 m

operating frequency: 868.42 MHz

Repeater function: Yes

### POWER SUPPLY

Frequency: 50 Hz ± 10 %

Nominal voltage: 230 V ± 10 %

Effective output: 1150 W

Power consumption: < 2 mA (without load)